

Biotrue® ONEday for Astigmatism parameters



Cilinder	LOW MINUS POWER 0.00D tot -6.00D (in stappen van 0.25D)				HIGH MINUS POWER -6.50D tot -9.00D (in stappen van 0.50D)				PLUS POWER +0.25D tot +4.00D (in stappen van 0.25D)			
	-0.75	-1.25	-1.75	-2.25	-0.75	-1.25	-1.75	-2.25	-0.75	-1.25	-1.75	-2.25
10°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
20°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
30°	✓	✓	✓									
40°	✓	✓	✓									
50°	✓	✓	✓									
60°	✓	✓	✓		✓	✓	✓					
70°	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	
80°	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓
90°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
100°	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	✓
110°	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓	
120°	✓	✓	✓		✓	✓	✓					
130°	✓	✓	✓									
140°	✓	✓	✓									
150°	✓	✓	✓									
160°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
170°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
180°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

✓ Beschikbaar oktober 2019

✓ Beschikbaar mid-november 2019

✓ Beschikbaar januari 2020